

1530.1530 Coco, coir and sisal tile with self laying backing

Specifications

rev May 2019

Specifications:

Quality:	Flat woven, loop pile
Pile composition:	65% coir, 35% sisal
Tile Size:	50x50 cm (20" x 20" nom.)
Carton size:	16 tiles/ctn or (approx. 43sf/ctn)
Secondary backing:	Self laying Bitumen-backing (code 56)
Thickness:	10.5 mm (approx. 1/2")
Pile weight:	2180 g/m ² (approx. 64 oz/yd ²)
Total weight:	6260 g/m ²
Resistance of heat conduction:	ISO 8302/0.10 m ² K/W
Tog Rating:	1.00
Sound insulation:	25 db
Traffic Class:	Commerical

If castor chairs are used, this carpet should be protected locally with chair mats.

Cleaning instructions:

1. Use cleaner such as Host, available at Aronson's Floor Covering.
2. Dry stains as quickly as possible with a blotting motion.

Installation instructions:

1. Before installation, the tiles should be acclimatized in the room where they will be installed.
2. For permanent wall to wall installations the tiles should be placed in a "checker-board" pattern per diagram below.
 - Use a pressure sensitive adhesive.
 - Start in the center of the room and expand to the outside.
 - An arrow is shown on the back of the tiles.
3. For temporary installations without adhesive, tiles can be loose laid.
 - The stability of the tiles can change in humid circumstances.

