

6999.6999 Pre-finished Commercial Cork Tiles Specifications

rev May 2019

Specifications:

Tile sizes:	11.8" x11.8" 11.8" x 35.4" 5.9" x 35.4"
Thickness:	3/16" or 5/16"
Limited Wear Warranty:	8-30 years
Critical Radiant Flux:	ASTM E648, Class II
Smoke Density:	ASTM E662 <340 pass
Coefficient of Friction:	ASTM D2047 - Dry 0..75 ASTM D2047 - Wet 0.65
Acoustical Behavior:	STC ASTM E90-09 6" slab, no ceiling 52dB
Acoustical Behavior:	IIC ASTM E2179-03 6" Slab, no ceiling 50 dB
Delta IIC (effect of flooring on IIC):	ASTM E2179-03 22dB Slip Coefficient exceeds UL and ADA Recommendations
Static Load Limit / PSI:	ASTM F970 Pass
Chemical Resistance:	ASTM F925 Excellent1
Bacterial Resistance:	ASTM G21 Resistant
CHPS Indoor Air Quality:	Compliant CA 01350 Yes Meets Test Requirement for Floor Score Certification CA 01350
Resistance to Cigarette Burns:	DIN 519611984 Yes
Forklift Traffic:	No
Oil and Grease Resistance:	No
Suitability for Castered Chairs:	Yes
Standard Specification for Cork:	Floor Tile ASTM F3008-13 Meets/Exceeds Specification