

# Designer Series Cork, Cork Tile Specifications

Revised: 05/01/23



Blocks



Blocks




Cable



Jumble



Small Strips



Tumbled



Pick-up Strips

Application:	Commercial
Fiber:	Cork tile
Colors:	6 colors
Tile size:	12" x 24" (305 x 610 mm) Custom sizes available: 12" x 12" (305 x 305 mm) 6" x 24" (152 x 610 mm) 12" x 36" (305 x 914 mm)
Thickness:	5/32" (4mm) 3/16" (4.8mm) 5/16" (8 mm)
Weight:	82 lbs/sf
Finish:	Smooth
Country of origin:	Portugal
Flammability	Fire Test ASTM - E648-08
Warranty:	Refer to Conditions of Contract for project warranty provisions
Environmental:	Greenguard gold certified Red list free, declare Mindful MATERIALS
Misc:	Ask us about FSC® Certified Cork Designer Series qualifies for purchase under the buy American Act.

**ARONSON'S** FLOOR COVERING

135 West 17th Street New York, NY 10011 T (212) 243 4993 aronsonsfloors.com

# Designer Series Cork, Cork Tile Maintenance

Revised: 05/01/23

- Ensure that adhesive has cured for recommended period of time prior to conducting initial maintenance. Remove any protective coverings prior to cleaning. Sweep or dust mop and vacuum flooring to remove any dirt, dust or debris.
  - Mix 6 - 7 oz. of Hilway Direct Neutral Cleaner per gallon of cool and clean potable water (1:20). Use a clean microfiber mop lightly dampened with the cleaning solution to clean the entire floor. Avoid wet mopping, puddling and pooling the cleaning liquid. Let solution stand for 5-10 minutes.
  - Use a clean mop to remove any and all excess cleaning solution. Rinse area with clean, cool water and a clean, lightly dampened mop to ensure that all cleaning residue has been removed. Allow area to dry completely before allowing foot traffic.
  - Do not use an auto-scrubber to clean floor unless an additional coat of finish has been applied on-site in order to prevent liquid from penetrating seams.
  - Ensure that initial maintenance and finish application (if necessary) has been conducted prior to conducting daily maintenance. Sweep or dust mop and vacuum flooring to remove any dirt, dust or debris. Do not use vacuums that have a beater bar or electric brooms with hard plastic bottoms or no padding, as this may cause discoloration, scratching and loss of sheen. When using a mop, use a two bucket system for cleaning - one bucket with cleaning solutions and another bucket with clean, potable water for rinsing.
  - If using a mop, mix 0.5-1 ounce or 20 mL (1:200) of Hilway Direct Neutral Cleaner per gallon of clean, potable water. Use a clean, damp mop to clean spills, build-up, dirty areas or overall cleaning. Avoid wet mopping, puddling and pooling of cleaning liquid.
  - If using an auto-scrubbing machine, mix 0.25-0.5 or 10 mL (1:400) of Hilway Direct Neutral Cleaner per gallon of warm and clean potable water. Clean floor while wet using a 22 gauge soft bristled scrubbing brush or a 3M 4100 White Super Polish Pad.
- Ensure flooring area is clean and that all cleaning residue has been removed (this may require rinsing with clean, cool water). Allow area to dry completely before allowing foot traffic.