

Night Time, Matting Specifications

02/22/24



Brown



Brown




Charcoal



Charcoal Splash



Dark Grey



Light Grey



Brown Sugar

Application:	Residential and commercial
Fiber:	Nylon
Colors:	6 colors
Custom colors:	N/A
Width:	6'-7" (2m)
Length:	82'-0" (25m)
Texture:	Cut pile
Pile weight:	9 kg/m ² (29.49 oz/ft ²)
Total weight:	30 kg/m ² (99 oz/ft ²)
Pile thickness:	1/4" (7 mm)
Total thickness:	3/8" (10 mm)
Flammability:	Class 1
Primary backing:	Vinyl
Country of origin:	EU
Critical radiant flux tests:	ASTM E648 Standard Test Method
Warranty:	3 years limited warranty
Environmental:	CRI, Green Label Plus Environmental Product Declaration available upon request

Night Time Collection, Broadloom Maintenance

Revised: 05/01/23

Precautions

- Follow facilities Standard Operating Procedures (SOP). All Safety Data Sheets and product label instructions must be read understood and followed prior to using the product.

Daily Cleaning

- Best Performed while matting is dry, vacuum clean using a commercial brush vacuum cleaner as often as required.

Spot Removal

- Remove spills and spots as soon as possible after they occur. Remove solid components using a scoop, liquids using a clean white cloth or tissue paper. Always treat the spot with a clean, damp cloth and work in the direction of the pile. Pat on the spot, do not rub. Let the spot dry then vacuum the treated area. If required, call in an expert who can prevent the carpet from getting damaged by using the right products for dried or hardened spots.

Gum Removal

- Use ice to harden the gum and scrape off as much as possible using a standard (blunt) putty knife. Then use a citrus solvent based spot remover to remove the remaining gum. Immediately rinse with clean water twice and pat dry with paper towels between rinses. Perform a "periodic cleaning."

Ice Melt Removal

- To prevent Ice Melt build-up, vacuum several times a day while the matting is exposed to it. Then perform a "Periodic Cleaning" when the weather improves.

Periodic Cleaning

- First perform the "Daily Cleaning", "Gum Removal" and "Spot Removal" as required.
- Deep clean the matting using the "Hot Water Extraction" method nu qualified professionals. This method removes deeply embedded soils and should be performed as often as needed based on traffic and soil levels (typically once or twice a year). When clear water is obtained during the extraction, the dirt has been removed from the matting.

Additional Information

- Do not use oils or silicones, acetone, strong alkaline cleaning agents, scouring powder, strong solvents, or abrasive cleaning pads, as these can damage the product.

These instructions supersede any verbal or written instructions from representatives and must be followed in order for the New York Collection warranty to be in effect.