

Stained Cork, Cork Tile Specifications

Revised: 05/01/23



Calm Grey



Calm Grey



Walnut




Absolute Black



Antiquity



Frost



Grappa



Infinity Blue



Redwood



Sandy White



Steel Green



American Walnut



Winterlude

Application:	Residential & Commercial
Colors:	12 colors
Custom colors:	Custom colors available
Tile size:	12" x 12" (305 mm x 305 mm) 12" x 24" (305 mm x 610 mm)
Thickness:	5/16" (8 mm)
Density:	≥ 500 kg/m ³ average
Residual indentation:	≤ 0.3
Weight:	0.9 lb/ft ²
Flammability:	Fire Test ASTM - E648-08 Class II
Country of origin:	Portugal
Warranty:	5 year renewable finish warranty for normal wear and tear Greenguard Gold Folmaldehyde-free

Stained Cork, Cork Tile Maintenance

Revised: 05/01/23

- Your cork floor is very well protected by four coats of MP765 varnish, but to prevent grit, sand and dirt from being ground into the floor and dulling and scratching the finish, as with any floor, keep the floor clean.
- Firstly, the cork floor should be kept clean by routine vacuuming.
- Clean with a damp mop using any good hardwood floor cleaner diluted 5 to 10% in water. These products are commonly found in any Home Depot, Lowes or any reseller of hardwood floors.
- Never wax or oil your cork floor, as this is a urethane-based finish.
- Spills should be wiped up immediately.
- Use walk-off mats at entrance doors and in front of kitchen sink is encouraged. Avoid rubber backed or other non-ventilated mats or rugs.
- Protect your floor from everyday use by installing felt or plastic protectors under "feet" of furniture.
- Caster-wheeled chairs should have wide casters, preferably in neoprene rubber.
- Observe re-finishing maintenance schedule, and re-finish the cork floor when high-traffic areas begin to show signs of wear.